

TENT COOPERATION TREATY

PCT

INTERNATIONAL SEARCH REPORT

(PCT Article 18 and Rules 43 and 44)

Applicant's or agent's file reference 3-284 ATTUA	FOR FURTHER ACTION see Notification of Transmittal of International Search Report (Form PCT/ISA/220) as well as, where applicable, item 5 below.	
International application No. PCT/EP 01/ 03918	International filing date (day/month/year) 06/04/2001	(Earliest) Priority Date (day/month/year) 06/04/2000
Applicant GIACOMINI S.p.A.		

This International Search Report has been prepared by this International Searching Authority and is transmitted to the applicant according to Article 18. A copy is being transmitted to the International Bureau.

This International Search Report consists of a total of 3 sheets.

☒ It is also accompanied by a copy of each prior art document cited in this report.

1. Basis of the report

- a. With regard to the **language**, the international search was carried out on the basis of the international application in the language in which it was filed, unless otherwise indicated under this item.

☐ the international search was carried out on the basis of a translation of the international application furnished to this Authority (Rule 23.1(b)).

- b. With regard to any **nucleotide and/or amino acid sequence** disclosed in the international application, the international search was carried out on the basis of the sequence listing :

☐ contained in the international application in written form.

☐ filed together with the international application in computer readable form.

☐ furnished subsequently to this Authority in written form.

☐ furnished subsequently to this Authority in computer readable form.

☐ the statement that the subsequently furnished written sequence listing does not go beyond the disclosure in the international application as filed has been furnished.

☐ the statement that the information recorded in computer readable form is identical to the written sequence listing has been furnished

2. ☐ **Certain claims were found unsearchable** (See Box I).

3. ☐ **Unity of invention is lacking** (see Box II).

4. With regard to the **title**,

☐ the text is approved as submitted by the applicant.

☒ the text has been established by this Authority to read as follows:

VALVE ACTUATOR FOR WATER HEATING/COOLING AND SANITARY SYSTEMS

5. With regard to the **abstract**,

☒ the text is approved as submitted by the applicant.

☐ the text has been established, according to Rule 38.2(b), by this Authority as it appears in Box III. The applicant may, within one month from the date of mailing of this international search report, submit comments to this Authority.

6. The figure of the **drawings** to be published with the abstract is Figure No.

☒ as suggested by the applicant.

☐ because the applicant failed to suggest a figure.

☐ because this figure better characterizes the invention.

1
☐ None of the figures.

INTERNATIONAL SEARCH REPORT

In Application No
PCT/EP 01/03918A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 F16K31/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 F16K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB 2 291 949 A (ROTORK CONTROLS) 7 February 1996 (1996-02-07) page 4, line 25 -page 5, line 25 figure 1 ---	1
A	GB 2 311 838 A (BAKER HUGHES INC) 8 October 1997 (1997-10-08) page 3, line 23 -page 4, line 23 figure 1 ---	1
A	US 3 258 985 A (C. E. JORDAN) 5 July 1966 (1966-07-05) column 2, line 44 -column 3, line 14 figures 1,2 --- -/--	1

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search

8 August 2001

Date of mailing of the international search report

16/08/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Ceuca, A-N

INTERNATIONAL SEARCH REPORT

In International Application No
PCT/EP 01/03918

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB 204 094 A (FREDERICK BRERETON HOLT; JAMES PHILIP CAMPBELL; VICKERS ELECTRICAL CO L) 17 September 1923 (1923-09-17) page 2, line 92 -page 3, line 22 figures 1,2 ---	1
A	DE 35 03 783 A (FORSCH STEFAN; RUSER JAKOB) 22 August 1985 (1985-08-22) page 8, line 34 -page 9, line 12 figures 1,2 -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

In International Application No

PCT/EP 01/03918

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB 2291949 A	07-02-1996	AT 167730 T	15-07-1998
		DE 69503136 D	30-07-1998
		DE 69503136 T	01-04-1999
		EP 0770193 A	02-05-1997
		ES 2117430 T	01-08-1998
		WO 9604494 A	15-02-1996
		JP 10507808 T	28-07-1998
		NO 964417 A	17-10-1996
		US 5865272 A	02-02-1999
GB 2311838 A	08-10-1997	AU 1667997 A	09-10-1997
		CA 2201661 A	04-10-1997
		NO 971526 A	06-10-1997
US 3258985 A	05-07-1966	DE 1500418 A	18-09-1969
		FR 1440692 A	16-08-1966
		GB 1091851 A	22-11-1967
GB 204094 A	17-09-1923	NONE	
DE 3503783 A	22-08-1985	NONE	

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
18 October 2001 (18.10.2001)

PCT

(10) International Publication Number
WO 01/77559 A1

(51) International Patent Classification⁷: **F16K 31/04**

[IT/IT]; Via Santuario, 19, I-29010 Madonna del Sasso (IT).

(21) International Application Number: PCT/EP01/03918

(74) Agent: **ZANELLA, Ireneo**; Zanella & Associati S.r.l., P.O. Box 98, I-22074 Lomazzo (IT).

(22) International Filing Date: 6 April 2001 (06.04.2001)

(25) Filing Language: English

(81) Designated States (*national*): AT, AT (utility model), BG, CA, CH, CN, CZ, DE, DE (utility model), DK, DK (utility model), ES, FI, FI (utility model), GB, GE, HR, HU, IN, LU, MX, NO, PL, PT, RU, SE, SI, SK, SK (utility model), TR, UA, US, YU.

(26) Publication Language: English

(30) Priority Data:
MI2000A000732 6 April 2000 (06.04.2000) IT

(71) Applicant (for all designated States except US): **GIACOMINI S.p.A.** [IT/IT]; Via per Alzo, 39, I-28017 S. Maurizio d'Opaglio (IT).

(84) Designated States (*regional*): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).


Declarations under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AT, BG, CA, CH, CN, CZ, DE, DK, ES, FI, GB, GE, HR, HU, IN,

[Continued on next page]

(54) Title: **VALVE ACTUATOR FOR WATER HEATING/COOLING AND SANITARY SYSTEMS**

(57) Abstract: An improved actuator (1) for water heating/cooling and sanitary systems comprises a miniaturized D.C. motor (2) with a mechanical clutch element (4), a first motor reducing unit (6) including a planetary reducing unit with a high gear ratio, a second reducing unit (14) for transforming a rotary movement into a reciprocating axial movement, and a supporting framework (29, 7, 9, 26) for supporting said components, and an electronic card (37) for controlling and driving said motor (2). A plurality of coupling adapters (33) allow the improved actuator (1) to be coupled to manifolds of different manufacturers.



WO 01/77559 A1



LU, MX, NO, PL, PT, RU, SE, SI, SK, TR, UA, YU, European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE, TR)

- as to the applicant's entitlement to claim the priority of the
earlier application (Rule 4.17(iii)) for the following design-
nationUS
- of inventorship (Rule 4.17(iv)) for US only

Published:

- with international search report

- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

5 VALVE ACTUATOR FOR WATER HEATING/COOLING AND SANITARY SYSTEMS

Background of the invention

The present invention relates to an improved actuator for water heating/cooling and sanitary systems, according to the preamble of Claim 1.

10 In the heating and sanitary system field, so-called "thermoelectric" shutters, including a substantially thermoexpandable element, for example a wax capsule which, as it passes from a solid to a molten status thereof, upon a heating operation, expands to cause a valve, manifold or the like shutter, to be driven from a closing position to an open position and vice-versa are already known.

Said prior thermoelectric actuators have, due to a corresponding small size of their expanding material capsules, a small size, thereby they can be assembled both on individual components, such as valves, and on manifolds including a plurality of shutters typically spaced with a pitch of or less than 50 mm.

20 However, while said prior actuators reliably operate in their opening/closing operations, they are affected by several drawbacks and disadvantages. At first, their shutter can be exclusively driven to open/closed positions, thereby preventing a continuous adjustment of the flow rate through the circuit coupled to said shutter. This would involve a low operating efficiency, for example in water heating/cooling systems, with a consequent large power consume and heating cost.

30 In fact, a single opening/closing mode of operation, cannot provide an optimal adjustment, for example, of the water

heating/cooling system to provide said system with the required operating flexibility, as could be achieved by modern available digital technologies, such as fuzzy logic, autotuning, and so on techniques.

5 Moreover, the heating of the wax material melting resistive element, requires a comparatively great current drain: for example, a manifold including 15 actuators would require a comparatively high power consume and related cost, and a wiring including wires having a correspondingly large cross-section.

10 A further drawback of prior thermoelectric actuators is that they have a comparatively long switching on time, thereby a large electric power is consumed for heating and melting the wax material. In particular, after a long off period, for example at the start of the heating/cooling season, said switching on time would
15 amount to 8-10 minutes, whereas, in the operation of the heating/cooling system, this time would amount to 4-5 minutes, with great variations depending on the environment conditions. Since the power drain of a prior thermoelectric actuator is of about 5W, and since, for multiple actuators, for example 15 and more in
20 manifold arrangements, said power drain proportionately increases, said prior thermoelectric actuators cannot be battery power supplied. Furthermore, said prior actuators must overcome the overlapping shutter resilient forces, for example of 15 Kg, thereby preventing said prior thermoelectric actuators from being replaced
25 by newly designed low cost actuators, suitable to replace said prior thermoelectric actuators, which are large series products.

 For larger size circuit valves, i.e. for comparatively large flow-rate circuits, so-called "electric" actuators are moreover known, which comprise an electric motor, such as a synchronous
30 motor or a step motor, which electric actuators, however, have a large size and a great electric drain, a motor-reducing unit being sometimes arranged between their motor and shutter. The overall

size of this prior electric actuators, on the other hand, is comparatively large, thereby they cannot be properly miniaturized to efficiently replace said prior thermoelectric actuators.

Furthermore, the electric actuators comprise many components and have a rather high cost; thus they cannot be used in water heating/cooling and sanitary system manifolds including spaced-apart shutters; this increased size, moreover, would negatively affect the installation of the mentioned components.

While the requirement of replacing prior thermoelectric actuators by other types of actuators allowing a continuous adjustment of the driven shutter controlled flow rate, while providing a less switch-on time, is well known in this field since 20 years, alternative actuators suitable to meet the above mentioned requirements have not been yet provided.

15

Summary of the invention

Accordingly, the aim of the present invention is to provide an improved actuator, of the above mentioned type, which, on a side, is free of the drawbacks and disadvantages of prior actuators and, on the other side, allows to perform a continuous adjustment of the shutter movement or stroke, while providing a very reduced switch-on time and electric drain.

Within the scope of the above mentioned aim, a main object of the present invention is to provide such an actuator construction which is very reliable in operation and has a long life, and can be made at a cost substantially like that of prior thermoelectric actuators.

According to one aspect of the present invention, the above mentioned aim and objects, as well as yet other objects, which will become more apparent hereinafter, are achieved by an improved actuator for water heating/cooling and sanitary systems, having the features of Claim 1.

Further improvements and advantageous embodiments are defined in the dependent claims.

The improved actuators according to the invention provide a lot of advantages. The use of a D.C. motor provides an optimum size/torque ratio, with a time consistent operation fully independent from the environment conditions. Moreover, since miniaturized D.C. low power motors, like those provided by the invention, are at present used in a very large series in the motor vehicle industry, they can be made at a very low cost. The high RPM of the D.C. motors is advantageously herein greatly reduced by a reducing unit which can be easily made from plastics materials, is noiseless and provides a reduction larger than 1000 with its diameter less than 15 mm, i.e. substantially equal to the diameter of a suitable miniaturized D.C. motor, thereby providing the desired and necessary small size for assembling on conventional manifolds having shutter pitches less than 50 mm. A further advantage is that of transforming, by a worm screw, the rotary movement of a planetary reducing unit into an axial reciprocating movement thereof, thereby further increasing the reduction ratio, on a side, and allowing said actuator, on the other side, to reliably drive shutters requiring high driving forces, for example larger than 15 Kg. A further advantage of the above mentioned miniaturized D.C. motors is the very low power drained thereby, of about 8 times less than that of prior thermoelectric actuators, affected by the above mentioned limits. This low consume feature, in addition to being advantageous from the power drain aspect, makes the actuator driven by a miniaturized D.C. motor very suitable for battery power supply arrangements.

Yet another advantage of the improved actuators according to the present invention is that, by properly adjusting the shutter displacement, it is possible, by using known digital timing methods, to provide very high efficiency heating/cooling systems,

depending on the user requirements, through the overall operation day. The required displacement or stroke variations are achieved in a very short time and reliable manner, in opposition to a 4-5 minute opening/closing switching time of prior thermoelectric actuators, and with an operation which is fully independent from the contingent requirement conditions. Moreover, the power drain is further limited by the fact that the switching on time of the motors can be reliably controlled by an easily constructed electronic card. Yet another advantage is that the invention uses a mechanical clutch preventing the motors from locking at their end of stroke positions, which, together with a reliable timing by the control electronics, provides the actuator with a long operating life, i.e. greater than 10 years. A further advantage is that the provided planetary reducing unit can be assembled in an automatic manner, thereby reducing the assembling time and, accordingly, the overall making cost. Yet another advantage is that a plurality of adapters are provided, allowing to assemble a respective actuator according to the invention on different types of existing manifolds.

Brief description of the drawings

Further characteristics, advantages and details of the improved actuator according to the present invention will become more apparent from the following disclosure with reference to the accompanying drawings, in which a preferred embodiment of the actuator according to the present invention, provided by a merely indicative example, is illustrated. In the drawings:

Figure 1 is an exploded view of the main components of the improved actuator according to the invention;

Figure 2 is a side elevation view of the improved actuator of Figure 1, in an assembled condition;

Figure 3 is a front view of the actuator;

Figure 4 is a top plan view of the actuator;

Figure 5 is a perspective view of the improved assembled actuator, in which, for simplicity, the cap covering the actuator according to the invention has been shown by the dash-dot
5 line only in Figure 2.

Description of the preferred embodiment

In the figures, like parts have been indicated by like reference numbers.

10 With reference at first to figure 1, the improved actuator according to the present invention has been generally indicated by 1. The actuator 1 comprises, housed in a framework construction to be disclosed in a more detailed manner hereinafter, an electric motor 2 which, according to the invention, is a miniaturized D.C.
15 motor, of a power less than 1 Watt, for example of a type used in the motor vehicle field, for operating, for example, rear mirrors. The output shaft 3 of the motor 2 is operatively coupled to a mechanical clutch, generally indicated by 4, and including, for example, a contoured circular element of a resilient material, for
20 example a spring steel.

The number 6 shows a first reducing unit, including, according to the invention, a planetary reducing element providing a high reducing ratio, for example larger than 1000. This can be achieved by an arrangement including three planetary gears, rotating about
25 two ring gears, of different tooth numbers, for example with a 1-tooth difference.

The mechanical clutch element 4 and first reducing unit are housed at first in a correspondingly contoured ring 7, in turn housed in a housing sleeve 8 of a middle support 9, on the base surface 11 of
30 which is likewise formed a bell housing 12, including a sleeve pinion 13 of a second reducing unit 14, further comprising a worm screw 16 which can be engaged with an inner thread 17 of the

pinion element 13, having pinion teeth 18. In the assembled condition, a gear wheel 19 meshes both with the pinion ring 18 and with the output pinion 25 of the first reducing unit 6. The number 22 shows the active end of the worm screw element 16, which end
5 22 is operatively engaged with the rod 23 of the element 24 cooperating with the shutter device, not shown, inside the valve or manifold fitting, also not shown.

The number 26 shows a support base, to which the middle support 9 can be affixed, for example by a snap type of engagement
10 of perimetrically arranged hook teeth 27. As shown in figure 1, the middle support 9 and support base 26 are formed with a plurality of recesses housing the components of the first and second reducing units 6 and 14, and the contoured ring 7, housing the clutch element 4 and motor 2, the assembly being properly located by the cage or
15 cartridge element 29 including four legs 31 having end contoured teeth 32 for snap engaging in corresponding recesses, not shown, formed in the support base 26.

In the example of figure 1, moreover, with the supporting base 26 an annular adapted 33 is likewise snap engageable, said
20 annular adapter 23 having two diametrically opposite hook portions 34 for bridging the diametrically opposite lugs 36, of the element 24 to be coupled to the shutter mechanism to be driven.

By providing a given number of correspondingly contoured adapters, it is possible to connect the improved actuator
25 according to the invention to a like number of, for example, manifolds of different makers.

Finally, the reference number 37 shows a circuit card supporting the components and circuitry for programmably controlling the motor, or actuator. This controlling electronics is not
30 herein disclosed in further details since it can be easily designed by those skilled in the art; this is also true for the related programming or setting components, which can be correspondingly easily

designed by those skilled in the art, to be assembled, for example, on the covering cap 38, for controlling an individual valve, or to be arranged a given distance from a manifold or the like.

Thus above mentioned supporting framework,
5 substantially comprises the cartridge element 29, middle support 9, support base 26 and covering cap 38.

The reference number 39 shows a top end portion of the worm screw 16, projecting from the bell housing 12 and adapted to operate as a position displaying element or index, visually
10 showing the position of the shutter, for example the closing, opening or middle position thereof. This is achieved, for example, by suitably coloring the ends 39 and providing a corresponding mirror through the covering cap 39; or the cap can be at least partially, or at a region thereof, clear.

15 According to the invention, moreover, said top end 39, or other portion of the worm screw element 16, can advantageously operate also as a driving element for driving a limit switch, not shown.

The power supply can indifferently be a battery power
20 supply, the batteries of which are for example housed in the covering cap 38, or supported at a spaced position, or a D.C. power supply, as is broadly known for power supplying driving electronic cards and electric components. As the motor 2 is power supplied, it rotatively drives the first reducing unit 6, through the mechanical
25 clutch arrangement 4, the output pinion 21 of said first reducing unit 6 in turn rotatively driving the second reducing unit 14, and, in dependence on the rotary direction of the motor 2, the worm screw 16 will being axially driven either upward or downward. This up/down movement of the worm screw element 16 likewise causes
30 a corresponding up/down movement of the shutter, not shown, with a consequent displacement through the overall opening and closing stroke thereof, or vice-versa.

In operation it has found that, prior miniaturized D.C. small motors, for example of a type used in motor vehicle rear mirrors, absorb or drain a power less than 0.6 W, i.e. eight times less than that drained by prior thermoelectric actuators. By these
5 small motors and the two reducing units according to the present invention, of which the first is of planetary type and advantageously comprises three planetary gears rotating about two gear wheels with a difference of 1 tooth from one another, a high reduction ratio, larger than 1000, with a diameter less than 15 mm, is obtained.
10 Moreover, by the second reducing unit operating as a movement transformer, i.e. transforming a rotary movement into an axial movement, by a threaded type of engagement, the improved actuators according to the invention allow to easily overcome shutter springing reacting forces greater than 15 Kg.

15 In this connection it should be apparent that the shutter reciprocating time, i.e. the adjustment time, is very short, fully independent from the environment conditions and free of inertial delays, which amounts to several minutes in prior thermoelectric actuators. This provides a great power saving.

20 Moreover, the improved actuators according to the invention can be advantageously driven by several recently designed adjustment systems, such as PI adjusting devices, (i.e. proportional-integral adjusting device), time modulation adjusting devices, and fuzzy logic based self-adapting adjusters. Moreover,
25 since the flow rate of heating/cooling systems can be easily adjusted, it is possible to substantially improve the performance and efficiency of said systems, from the power consume and environmental aspect standpoints, i.e. depending on a plurality of requirements through an overall operating day.

30 Advantageously, moreover, the provision of a mechanical clutch prevents the motor from being locked as its end of stroke or limit positions, which greatly reduces the stresses applied to the motor,

thereby a very long operating life, greater than ten years, can be easily achieved.

Owing to the disclosed constructional arrangement, and the provision of reducing unit components made of a synthetic material, a noiseless operation and low costs can moreover be
5 achieved, which, together with a synthetic material construction of the portions of the support framework and covering cap, and low cost of the commercially available miniaturized D.C. motors, provides, on a side, a making cost substantially like that of prior
10 thermoelectric actuators and, on the other hand, a very small size actuator, which can be easily installed even on manifolds having shutters with a pitch less than 50 mm.

From the above constructional and operating disclosure, it should be apparent that the improved actuators
15 according to the present invention efficiently achieve the above mentioned aims, objects and advantages.

In practicing the invention, those skilled in the art can easily carry out modifications and variations, for example related to the arrangement of the reducing units and so on, and freely choose
20 the materials for the actuator components, and specifically designed control cards or program settings, without departing from the scope of the invention.

CLAIMS

1. An improved actuator for water heating/cooling and sanitary systems, including a driving motor and a related reducing unit operating on a spring preloaded shutter driving a component such as a valve, manifold or the like, **characterized** in that said actuator comprises, in a support framework,
- a) an electric motor comprising a miniaturized D.C. motor,
 - b) a first reducing unit comprising a planetary reducing unit providing a high reduction ration,
 - c) a second reducing unit arranged between the first reducing unit and an element operatively associated to the shutter, said second reducing unit including a worm screw for transforming a rotary movement into an axially reciprocating movement,
 - d) a mechanical clutch element, operatively arranged between an output of said D.C. motor and an inlet of said first planetary reducing unit,
 - e) an electronic control card for controlling and driving said D.C. motor depending on a presettable heating/cooling program, and
 - f) mechanic coupling means for coupling to said valve, manifold or the like, including the shutter to be driven.
2. An improved actuator according to claim 1, **characterized** in that said miniaturized D.C. electric motor comprises a D.C. small motor having a power drain less than 1 W, preferably less than 0,6 W, and with an outer diameter equal to or less than 15 mm.
3. An improved actuator according to Claim 1, **characterized** in that the first planetary reducing unit provides a reduction ratio greater than 1000, and that said first planetary reducing unit comprises three planetary gears rotating about two gear rings, said gear rings having a different number of teeth, preferably one of said gear ring having 1 tooth less than the other

gear ring, to provide a different RPM.

4. An improved actuator according to Claim 1, **characterized** in that said second reducing unit comprises a driving gear wheel and a second gear wheel or pinion having an inside threaded sleeve and housing with a threading engagement a worm screw element to transform a rotary movement into an axial reciprocating movement, wherein said worm screw element has an end operatively cooperating with a rod, or the like, of the shutter driving element.

5. An improved actuator according to Claim 4, **characterized** in that said worm screw element has, at a top thereof, a further end visually projecting from a bell housing support and operating as a visual element for visually indicating the position of said shutter and/or as a limit switch driving element.

6. An improved shutter according to Claim 1, **characterized** in that said shutter comprises a support framework including a middle support supporting said first reducing unit with said mechanical clutch and said second reducing unit, a support base which can be coupled to said middle support, and a cage element having legs which can be plugged in said support base for protecting said electric D.C. motor.

7. An improved actuator according to one or more of the preceding claims, **characterized** in that it comprises a covering cap which can be coupled, preferably in a removable manner, for example by a snap type of engagement, to said actuator support framework.

8. An improved actuator according to Claim 7, **characterized** in that said covering cap is made, at least at a region thereof, of a clear material to detect a position of a signaling element indicating the instantaneous position of said shutter.

9. An improved shutter, according to Claim 1, **characterized** in that said mechanical coupling means for coupling

to said valve, manifold or the like, comprise a plurality of differently arranged adapters each of which can be coupled to a valve, manifold or the like of a desired maker.

1 / 3






FIG.1

2 / 3



3 / 3




FIG. 4




FIG. 5